

Communication Box /NB-IoT

Description

The CN100 is responsible for receiving sensor data from any sensor station , receiving geographic coordinates (Every 24 hours) and sending it to the server via the LoRaWAN protocol.



Specifications	
Hardware Specification	Processor: ST (L Series) NB-IoT Module: ESM-Alborz GPS Chipset: Qualcomm
Connectors	4 Pin: Programmer Connector 6 Pin: communication bus SMA Connector(Left, Top view): GPS Antenna SMA Connector(Right, Top view): NB Antenna
Working Environment	Operating Temperature : -40°C ~ 85°C Operating humidity : 0 ~ 100%
Processor Specification	Arm® 32-bit Cortex®-M0+ with MPU – From 32 kHz up to 32 MHz max. – 0.95 DMIPS/MHz - Ultra low power
NB-IoT Specification	Supported Frequency Bands: LTE bands B1, B3, B5, B8, B20 RF Sensitivity: -135 dBm TX Power: +23 dBm
GPS Specification	Support: GPS, GLONASS, BeiDou, Galileo and QZSS Ultra low power consumption Tracking Sensitivity: -165dbm
Battery Specification	Nominal capacity: 13.0 Ah Nominal Voltage: 3.6 V (at 2 mA +20°C) self-discharge rate: less than 3% after 1 year of storage at +20°C Maximum recommended continuous current: 1800 mA
Power	Input Universal Range 3.3-3.7 DC (Li-ion Battery)
Power Consumption	<500mW
Case	Waterproof (IP67) with military Connectors
Physical Features	75*125*110 mm